

Declaration of performance

Icopal Universal, SA & FM (EN 13707)

UNIQUE IDENTIFICATION CODE OF THE PRODUCT TYPE

0100.10

Icopal Universal, SA & FM (EN 13707)

INTENDED USE OR USES

Bitumen membrane for waterproofing

MANUFACTURER

ICOPAL BV
Hoendiep 316, 9744 TC Groningen
Netherlands

SYSTEM OR SYSTEMS AVCP

System 2+

HARMONISED TECHNICAL SPECIFICATION

EN 13707:2013

NOTIFIED BODY/IES

0620

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Groningen

02-08-2021



DECLARED PERFORMANCE

ESSENTIAL CHARACTERISTICS	PERFORMANCE
External fire performance	F roof *
Reaction to fire	Class E
Watertightness	Pass (300 kPa)
Tensile strength longitudinal	1250 ± 20% N/50 mm
Tensile strength transverse	1050 ± 20% N/50 mm
Elongation longitudinal	30 ± 15 % abs.
Elongation transverse	35 ± 15 % abs.
Root resistance	NPD
Resistance to static load method A	≥ 20 kg
Resistance to static load method B	≥ 10 kg
Resistance to static load method C	NPD
Resistance to impact method A	≥ 1250 mm
Resistance to impact method B	≥ 1250 mm
Resistance to tearing	300 +250/-0 N
Peel resistance of joints	50 +100/-0 N
Shear resistance of joints	800 +700/-0 N
Durability UV heat and water	Grade 0
Durability: heat flow after heat oven exposure	150 +30/-0 °C
Durability: flexibility at low temperature after heat oven exposure	-25 +0/-10 °C
Flexibility at low temperatures	≤ -25 °C
Dangerous substances	Note 1&2

Note 1: This product does not contain asbestos or tar constituents

Note 2: In the absence of European harmonized test methods, verification and declaration on release/content has to be done taken into account national provisions in the place of use.

*: since the external fire performance of a roof is dominated by the built up system, no performance can be assessed for the product alone

BMI icopal

Hoendiep 316
9744 TC Groningen
Phone: +31 50 551 6333

www.bmigroup.com/nl