

Declaration of performance

VEDATOP SU

UNIQUE IDENTIFICATION CODE OF THE PRODUCT TYPE

4394.3

VEDATOP SU

INTENDED USE OR USES

bitumen membrane for basement

MANUFACTURER

ICOPAL BV
Hoendiep 316, 9744 TC Groningen
Netherlands

SYSTEM OR SYSTEMS AVCP

System 2+

HARMONISED TECHNICAL SPECIFICATION

EN 13969:2004/ A1:2006

NOTIFIED BODY/IES

1213

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Groningen

01-02-2021



DECLARED PERFORMANCE

ESSENTIAL CHARACTERISTICS	PERFORMANCE
External fire performance	F roof *
Reaction to fire	Class E
Reaction to fire	Class E
Watertightness at 2kPa	NPD
Watertightness at 60kPa	NPD
Watertightness	Pass (200 kPa)
Tensile strength longitudinal	1100 ± 20% N/50 mm
Tensile strength longitudinal	1100 ± 20% N/50 mm
Tensile strength transverse	1100 ± 20% N/50 mm
Tensile strength transverse	1100 ± 20% N/50 mm
Elongation longitudinal	5 ± 3 % abs.
Elongation longitudinal	5 ± 3 % abs.
Elongation transverse	5 ± 3 % abs.
Elongation transverse	5 ± 3 % abs.
Resistance to static load method B	NPD
Root resistance	NPD
Resistance to impact method A	NPD
Resistance to static load method A	NPD
Resistance to impact method B	NPD
Resistance to static load method B	NPD
Resistance to tearing	NPD
Resistance to static load method C	NPD

Note 1: This product does not contain asbestos or tar constituents

Note 2: In the absence of European harmonized test methods, verification and declaration on release/content has to be done taken into account national provisions in the place of use.